



Fig. 0586T00 NPTF Threaded Fill Limit Valve (FLV)

CONSTRUCTION:

- Machined aluminum
- Blue polymer valve
- Standard ullage depths range from 3/8" to 1-1/2"
- For mounting on aluminum tanks
- See page E-10 for more FLV information



Technical Information

Catalog No.	Length Inches	Width Inches	Projection Inches	Ullage Depth Inches*	Hose Connection Inches	Mounting Hole Dia. Inches
0586T00038	3-31/32	1-5/16	1-1/4	3/8	5/8	1" NPTF
0586T00034	4-11/32	1-5/16	1-1/4	3/4	5/8	1" NPTF
0586T00118	4-23/32	1-5/16	1-1/4	1-1/8	5/8	1" NPTF
0586T00112	5-3/32	1-5/16	1-1/4	1-1/2	5/8	1" NPTF

Ordering Information - OEM Bulk Pkg. 10 Pcs.

Catalog No.	Style	Ullage Depth Inches	Collar	For Use on Tank Type	Angle Port	Fire Test Capable	Shipping Weight Lbs.
0586T00038	NPTF, Threaded	3/8	No	Aluminum	90°	Yes	2.6
0586T00034	NPTF, Threaded	3/4	No	Aluminum	90°	Yes	2.9
0586T00118	NPTF, Threaded	1-1/8	No	Aluminum	90°	Yes	3.4
0586T00112	NPTF, Threaded	1-1/2	No	Aluminum	90°	Yes	4.1

*Note: Longer shut-off heights in 1/2" increments are generally available up to 5-1/2". For custom heights, contact the factory.