

Removable Bi-Color Pole Lights with Utility Lights

2-mile (USCG 2nm) Certified - Patent No. 4,500,947
Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer Top
 Finish: Black Top and Collar
 Pole Rake: 1421: 0°
 1422: 5°
 Contacts: Gold Plated
 Tube: 3/4" Anodized Aluminum
 Collar: Locking
 Voltage: 12V (Bulb Included)
 Wattage: 10 watts
 Amperage: .80 amps
 Base (3-Pin): 1421: 1045 & 1047
 1422: 1060
 Features: Deck Illuminating Utility Light



Fig. 1421
0° Rake

Fig. 1422
5° Rake

Fig. 1421
(Shown)

Pole Length	Retail Pkg.	OEM Bulk Pkg.
12"	1421DP2CHR	1421002CHR
17-1/4"	1421DP3CHR	1421003CHR
12"	1422DP2CHR	1422002CHR



1-mile (USCG 1nm) Certified - Patent No. 4,500,947
Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Zinc Alloy and Polymer Top
 Finish: Black Top and Collar
 Pole Rake: 1211: 0°
 1212: 5°
 Tube: 3/4" Anodized Aluminum
 Contacts: Gold Plated
 Collar: Locking
 Voltage: 12V (Bulb Included)
 Wattage: 10 watts
 Amperage: .80 amps
 Base (3-Pin): 1211: 1045 & 1047
 1212: 1060
 Features: Deck Illuminating Utility Light



Fig. 1211
0° Rake

Fig. 1212
5° Rake

Fig. 1212
(Shown)

Pole Length	Retail Pkg.	OEM Bulk Pkg.
12-1/2"	1211DP2CHR	1211002CHR
12-1/2"	1212DP2CHR	1212002CHR



Removable bi-color lights on pages 14 and 15 are ideal for boats with casting decks on the bow. Unlike conventional bi-color lights that can stand as high as 2" above the deck, removable bi-color lights can be unplugged and stowed while fishing. This leaves only a small, flat topped base. Longer lengths are designed for use with larger trolling motors.

Compatible Bases (2 Pin)

Fig. 1045
0° Rake



Fig. 1047
0° Rake



Fig. 1060
5° Rake



Bases Sold Separately - See Pages 58 & 59.

Spare Parts Information

Figs. 1211, 1212, 1421 & 1422:

Bulbs: 0071DP0CLR.

Utility Light Bulb: 0064000CLR.

Lens Set Figs.

1211 & 1212 : 0268DP0LNS.

Welded Lens Set Figs. 1421 & 1422

(Black Top) : 0241DP0LNS.



Fig. 0071DP0CLR



Fig. 0268DP0LNS



Fig. 0241