



# Navigation Lights

**For Vessels 20m (65.6 ft) to 50m (164.0 ft.)**

For 12 and 24 volt VDC or 120 VAC systems,  
Black or White Polymer



**Fig. 1377  
Side Lights**



**Fig. 1378  
Masthead Light**



**Fig. 1379  
White Stern or  
Yellow Towing Lights**



**Fig. 1380  
White, Yellow,  
Green or Red  
All Round Lights**

## ORDERING INFO

Black Polymer Description	Visibility Arc	Visibility Miles	120 VAC		12/24 VDC		Ship Wt. Carton Lbs. Standard Pkg.
			Black Polymer Std. Pkg. 1 Pc.	Black Polymer Std. Pkg. 1 Pc.	Black Polymer Std. Pkg. 1 Pc.	Black Polymer Std. Pkg. 1 Pc.	
Red Side Light	112-1/2°	2	1377R00BLK	1377R01BLK	1377R01BLK	1377R01BLK	3.2
Green Side Light	112-1/2°	2	1377G00BLK	1377G01BLK	1377G01BLK	1377G01BLK	3.2
White Masthead Light	225°	5	1378000BLK	1378001BLK	1378001BLK	1378001BLK	3.1
White Stern Light	135°	2	1379000BLK	1379001BLK	1379001BLK	1379001BLK	3.2
Yellow Towing Light	135°	2	1379M00BLK	1379M01BLK	1379M01BLK	1379M01BLK	3.2
White All-Round Light	360°	2	1380000BLK	1380001BLK	1380001BLK	1380001BLK	3.0
White All-Round Light**	360°	5	1380H00BLK	1380H01BLK	1380H01BLK	1380H01BLK	3.0
Red All-Round Light	360°	2	1380R00BLK	1380R01BLK	1380R01BLK	1380R01BLK	3.0
Green All-Round Light	360°	2	1380G00BLK	1380G01BLK	1380G01BLK	1380G01BLK	3.0
Yellow All-Round Light	360°	2	1380M00BLK	1380M01BLK	1380M01BLK	1380M01BLK	3.0

  

White Polymer Description	Visibility Arc	Visibility Miles	120 VAC		12/24 VDC		Ship Wt. Carton Lbs. Standard Pkg.
			White Polymer Std. Pkg. 1 Pc.	White Polymer Std. Pkg. 1 Pc.	White Polymer Std. Pkg. 1 Pc.	White Polymer Std. Pkg. 1 Pc.	
Red Side Light	112-1/2°	2	1377R00WHT	1377R01WHT	1377R01WHT	1377R01WHT	3.2
Green Side Light	112-1/2°	2	1377G00WHT	1377G01WHT	1377G01WHT	1377G01WHT	3.2
White Masthead Light	225°	5	1378000WHT	1378001WHT	1378001WHT	1378001WHT	3.1
White Stern Light	135°	2	1379000WHT	1379001WHT	1379001WHT	1379001WHT	3.2
Yellow Towing Light	135°	2	1379M00WHT	1379M01WHT	1379M01WHT	1379M01WHT	3.2
White All-Round Light	360°	2	1380000WHT	1380001WHT	1380001WHT	1380001WHT	3.0
White All-Round Light**	360°	5	1380H00WHT	1380H01WHT	1380H01WHT	1380H01WHT	3.0
Red All-Round Light	360°	2	1380R00WHT	1380R01WHT	1380R01WHT	1380R01WHT	3.0
Green All-Round Light	360°	2	1380G00WHT	1380G01WHT	1380G01WHT	1380G01WHT	3.0
Yellow All-Round Light	360°	2	1380M00WHT	1380M01WHT	1380M01WHT	1380M01WHT	3.0

Special lights to meet local requirements are available upon request

\*\*For Great Lakes use

## TECH INFO

- L.E.D.: Operates on 12 and 24 VDC or 120 VAC Systems
- No user serviceable parts
- Screw Size: 1/4"
- Height Overall: 6"
- Height Lens: 3-1/2"

MARINE NAVIGATION LIGHT CERTIFIED TO THE USCG AND '72 COLREGS BY IMANNA LABS IN ACCORDANCE WITH A.B.Y.C. A-1104. FOR USE ON VESSELS 20 METERS TO 50 METERS.

